

RT250 Thin Client Spec. List

品名	RT250C / L	RT250X
Board Level		
CPU	VIA Eden 533 MHz CPU	VIA Eden 533 MHz CPU
Companion Chip	VIA VT8606 North bridge + VT8231 South bridge	
Graphic Chip	Integrated 2D/3D/Video Accelerator, Max supports 1600*1200, 16-bit	
LAN	Integrate Ethernet controller with VIA VT6103 PHY Supports 10/100Base-T Ethernet	
Audio	VIA A'97codec	
RAM	64MB SO-DIMM , Max supports 512MB SDRAM	256MB SO-DIMM , Max supports 512MB SDRAM
Flash Memory	32MB DOM , Max supports 512MB DOM	384MB DOM , Max supports 512MB DOM
ROM	2Mbboot ROM	
I/O Supports		
VGA	One port 15-pin D-Sub CRT VGA	
LAN	One port RJ45 10/100Mbps Ethernet	
PCI	One mini-PCI slot	
IDE	One UltraDMA-33/66/100 IDE interface , supports 2.5"IDE HDD	
Parallel Port	One 25-pin D-Sub Parallel port	
Serial Port	One RS-232 Header	
PS2	Two PS2 ports	
Audio	Output: 1/8-inch mini, full 16 bit stereo, 48KHz sample rate Input: 1/8-inch 8 bit mini microphone level	
USB	Two USB ports , supports internal3 rd and4 th USB Ports Interface Header (Option USB Wireless module for Linux or XPE)	
CPU FAN	FAN Less	
Wireless LAN	Supports mini-PCI WLAN Module(Optional)	
Power	12V/DC 4A Adapter	
Software		
OS	1. Windows CE.Net4.2 (English/Chinese) 2. Embedded Thin DOM Linux	Windows XP Embedded (English/Chinese) Supports RAM / DISK Type
Network	1. TCP/IP With DNS and DHCP RDP5.1 /ICA 6.2(STD Shell only) 2. TCP/IP With DNS and DHCP Supports RDP5.1/ICA 7.0/XDMCP/VNC View	TCP/IP with DNS and DHCP , RDP5.1 , Supports NDS 、 Citrix ICA6.2 / 7.0(Optional) ,
Equipment	Supports USB Floppy 、 USB COMO 、 USB Printer	Supports Smart Card Reader 、 USB COMO 、 USB Floppy 、 USB Zip 、 USB Hard Disk 、 USB Printer
Application	1.IE6.0 、 Media Player 9.0 2.Opera	IE 6.0 , Media Player 8.0 , Word pad Shockwave Flash 、 Messenger 、 Net-meeting